



# project check lists concrete pour

use in conjunction with the specification for the subject project



## INTRODUCTION

It is difficult during a visit to a construction site to memorise all of the details that need to be checked and while the obvious ones stand out, many other items that should be checked are forgotten. Supervisors may get distracted or over extended due to time constraints and overlook items that may have more serious consequences later in the project.

These Check Lists provide a guide to the inspections that are required on site for a particular project. They are a précis of the full clauses in the project specification and can be referred back to the specification if the full text of the particular item is required. The Check Lists will remind you of virtually every potential problem in materials, workmanship and coordination between trades.

The Check Lists include a list of the Hold Points, Witness Points and Tests that are required to be signed off by the Supervisor on projects that include the Project Control section. The rest of the checks are simply dot points to jog the memory of the Supervisor.

Project specific checks may be added to the Check Lists for individual projects and the experience of Supervisors can be shared by the addition of particular checks on items or operations that are generally of concern on site. In this case less experienced Supervisors can use these Check Lists to provide them with the back up of more experienced officers.

Provide one copy of the Check Lists book to the Supervisor and one copy to the Contractor for the particular project.

### **HOW TO USE THESE CHECK LISTS**

Take photocopies of the relevant Check List sections before going on site and study these. This book of Check Lists is spiral bound to allow pages to be photocopied easily.

Mark any items in the Check List that are of particular concern.

At the project site, check off the work against the Check Lists and make notes of any action required in the space provided.

When the work is completed and the final check has been made sign off and date in the box provided. There is also space to provide comments.

Keep a record of all of the completed Check Lists for future reference if required. These could prove to be valuable if disputes arise on the project.

There is no better way to document actual site conditions or details than by photographs, so don't forget to take a digital camera on site and take images to go with particular items in the Check lists.

### **FURTHER DEVELOPMENT**

If you have any suggestions to improve on these Check Lists or the system in general please contact Lawrie Foscaro, Manager, Specification Services, 3rd Floor Highway House, Palmerston. Tel; 8946 5021 or email DocumentationServices.Dol@nt.gov.au.

Doc ID	Version	Issued	Printed	Page
1.04–PCL Concrete Pour	2016.03	Sept 2016	19/09/2016	2 of 4





Comments from in-house staff, consultants or contractors are most welcome.

# **CONCRETE POUR CHECKLIST**

Project/Job Name: Contract No: Audit Date: Contractor: Concrete Supplier:

Mix Design Approved/Not Approved

	Audit Item	Υ	N	Comments
	1. Preliminary			
•	Description			
•	Lot Number/s			
•	Previous Lots Conform			
•	Casting Program Accepted			
•	Curing Method			
	(Stream) (Water) (Fog) (Other)			
	O. Farmonia and Falancia			
	2. Formwork and Falsework			
•	Formwork Dimensions in Accordance with Design, including void lengths			
•	Forms Clean, Smooth and Watertight and Free			
	of Deleterious/Extraneous/Foreign Materials			
•	Formwork within Dimension Tolerances			
•	Forms Meet Line and Level Requirements			
	O. Daintanain a Otaal			
	3. Reinforcing Steel			
•	Steel Located/Fixed in Accordance with Drawings			
•	Reinforcing Clean and Free of Deleterious Materials			
•	Critical Cover of 30mm Checked at all locations			
•	All Splices to Reinforcement at Approved Locations			
•	All Welds in Accordance with Australian Standards and RFT			
	4. Concrete Inclusions			
•	Embedded Dowels, Bolts, Conduits and Ducts			
•	Cored Holes, Weepholes, Block Outs,			
•	transverse stressing holes Lifting/Carrying Lugs etc			
•	Located as Shown on Drawings			
	Audit Results	and	Comi	l monte
	Audit nesults	anu	COIIII	IIIGIIIS
Sig	nature:		Date	

Doc ID	Version	Issued	Printed	Page
1.04–PCL Concrete Pour	2016.03	Sept 2016	19/09/2016	3 of 4



S. Concrete Delivery  Number of Batches Batch Time (From Delivery Docket) Batch Time (From Delivery Docket) Finish Time  6. Concrete Testing NATA Approved Testing Authority Ambient Temperature (Between 5°C and 35°C) Actual Concrete Temperature Actual Concrete Temperature Target Slump 50 mm ± 10mm. Actual Slump Amount of Admixture added Amount of Marikture added Amount of water added Number of Cylinders Taken Target Strength  7. Concrete Placement Placement Method (Pump, Tremie, Chute, Other) Other) Sufficient Personnel for Finishing etc. Approved Vibration Method Back up Vibrators on Hand Reinforcement Cover Maintained During Pour Formwork Stable During Placing and Vibration Provision for Closure of Access/Openings Forms Free of Foreign Matter Prior to Pouring Concrete Flaced and Compacted Within: 28°C – 28°C – 28°C – 55°C et 86 mins 32°C – 28°C – 55°C et 86 mins Addit Results and Comments  Signature:  Date		Audit Item	Υ	N	Comments		nts
Batch Time (From Delivery Docket) Arrival Time at Site Finish Time  6. Concrete Testing NATA Approved Testing Authority Ambient Temperature (Between 5°C and 35°C) Actual Concrete Temperature Target Slump 50 mm ± 10mm. Actual Slump Amount of Admixture added Amount of water added Amount of water added Number of Cylinders Taken Target Strength  7. Concrete Placement Placement Method (Pump, Tremie, Chute, Other) Sufficient Personnel for Finishing etc. Approved Vibration Method Back up Vibrators on Hand Reinforcement Cover Maintained During Pour Formwork Stable During Placing and Vibration Concrete Placed and Compacted Within: 28°C - 28°C - 75mins 28°C - 28°C = 60 mins 32°C - 35°C = 45 mins Provision for Closure of Access/Openings Forms Free of Foreign Matter Prior to Pouring Forms Free of Foreign Matter Prior to Pouring Audit Results and Comments							
Arrival Time at Site     Finish Time     In 2. 3.     Finish Time     In 2. 3.      G. Concrete Testing     NATA Approved Testing Authority     Ambient Temperature (Between 5°C and 35°C)     Actual Concrete Temperature     In 2. 3.     Target Slump 50 mm ± 10mm. Actual Slump     In 2. 3.     Amount of Admixture added     In 2. 3.     Amount of Admixture added     In 2. 3.     Amount of water added     In 2. 3.     Number of Cylinders Taken     Target Strength      Toconcrete Placement     Placement Method (Pump, Tremie, Chute, Other)     Sufficient Personnel for Finishing etc.     Approved Vibration Method     Back up Vibrators on Hand     Reinforcement Cover Maintained During Pour     Formwork Stable During Placing and Vibration     Concrete Placed and Compacted Within:     25°C - 28°C = 75mins     28°C - 35°C = 60 mins     32°C - 35°C = 45 mins     Audit Results and Comments	•	Number of Batches					
Finish Time  6. Concrete Testing  NATA Approved Testing Authority Ambient Temperature (Between 5°C and 35°C)  Actual Concrete Temperature 1. 2. 3.  Target Slump 50 mm ± 10mm. Actual Slump  1. 2. 3.  Amount of Admixture added 1. 2. 3.  Amount of water added 1. 2. 3.  Number of Cylinders Taken Target Strength  7. Concrete Placement Placement Method (Pump, Tremie, Chute, Other)  Sufficient Personnel for Finishing etc. Approved Vibration Method Back up Vibrators on Hand Reinforcement Cover Maintained During Pour Formwork Stable During Placing and Vibration Concrete Placed and Compacted Within: 25°C - 28°C = 75mins 28°C - 35°C = 45 mins 32°C - 35°C = 45 mins 32°C - 35°C = 45 mins Audit Results and Comments	•	Batch Time (From Delivery Docket)			1.		
S. Concrete Testing  NATA Approved Testing Authority  Ambient Temperature (Between 5°C and 35°C)  Actual Concrete Temperature  Target Slump 50 mm ± 10mm. Actual Slump  Target Slump 50 mm ± 10mm. Actual Slump  Amount of Admixture added  Amount of water added  Target Strength  T. Concrete Placement  Placement Method (Pump, Tremie, Chute, Other)  Sufficient Personnel for Finishing etc.  Approved Vibration Method  Back up Vibrators on Hand  Reinforcement Cover Maintained During Pour  Formwork Stable During Placing and Vibration  Concrete Placed and Compacted Within:  25°C - 28°C = 75mins  28°C - 32°C = 60 mins  32°C - 35°C = 45 mins  28°C - 32°C = 65 mins  32°C - 35°C = 45 mins  Audit Results and Comments	•	Arrival Time at Site			1.	2.	3.
NATA Approved Testing Authority     Ambient Temperature (Between 5°C and 35°C)     Actual Concrete Temperature     Target Slump 50 mm ± 10mm. Actual Slump     Target Slump 50 mm ± 10mm. Actual Slump 50 mm	•	Finish Time			1.	2.	3.
NATA Approved Testing Authority     Ambient Temperature (Between 5°C and 35°C)     Actual Concrete Temperature     Target Slump 50 mm ± 10mm. Actual Slump     Target Slump 50 mm ± 10mm. Actual Slump 50 mm							
Ambient Temperature (Between 5°C and 35°C)     Actual Concrete Temperature     Target Slump 50 mm ± 10mm. Actual Slump     Target Slump 50 mm ± 10mm. Actual Slump     Target Slump 50 mm ± 10mm. Actual Slump     Amount of Admixture added     Amount of water added     Target Strength     Target Strength     Target Strength     Target Strength     Sufficient Personnel for Finishing etc.     Approved Vibration Method     Back up Vibrators on Hand     Reinforcement Cover Maintained During Pour     Formwork Stable During Placing and Vibration     Concrete Placed and Compacted Within:     25°C – 28°C = 75mins     28°C – 32°C = 60 mins     32°C – 35°C = 45 mins     Provision for Closure of Access/Openings     Forms Free of Foreign Matter Prior to Pouring     Concrete Finished to Approved Tolerances  Audit Results and Comments		6. Concrete Testing					
Actual Concrete Temperature     Target Slump 50 mm ± 10mm. Actual Slump     1.     2.     3.      Amount of Admixture added     1.     2.     3.      Amount of water added     1.     2.     3.      Amount of Viniders Taken     Target Strength      7. Concrete Placement     Placement Method (Pump, Tremie, Chute, Other)     Sufficient Personnel for Finishing etc.     Approved Vibration Method     Back up Vibrators on Hand     Reinforcement Cover Maintained During Pour     Formwork Stable During Placing and Vibration     Concrete Placed and Compacted Within:     25°C - 28°C = 75mins     28°C - 35°C = 45 mins     Provision for Closure of Access/Openings     Forms Free of Foreign Matter Prior to Pouring     Concrete Finished to Approved Tolerances  Audit Results and Comments	•				Name:		
Target Slump 50 mm ± 10mm. Actual Slump  Amount of Admixture added Amount of water added Amount of water added Amount of Cylinders Taken Target Strength  T. Concrete Placement Placement Method (Pump, Tremie, Chute, Other) Sufficient Personnel for Finishing etc. Approved Vibration Method Back up Vibrators on Hand Reinforcement Cover Maintained During Pour Formwork Stable During Placing and Vibration Concrete Placed and Compacted Within: 25°C - 28°C = 75mins 28°C - 25°C = 45 mins 32°C - 35°C = 45 mins Provision for Closure of Access/Openings Forms Free of Foreign Matter Prior to Pouring Concrete Finished to Approved Tolerances  Audit Results and Comments	•	Ambient Temperature (Between 5°C and 35°C)					
Amount of Admixture added     Amount of water added     Amount of water added     Incomparison of Cylinders Taken     Target Strength      Concrete Placement     Placement Method (Pump, Tremie, Chute, Other)     Sufficient Personnel for Finishing etc.     Approved Vibration Method     Back up Vibrators on Hand     Reinforcement Cover Maintained During Pour     Formwork Stable During Placing and Vibration     Concrete Placed and Compacted Within:     25°C - 28°C = 75mins     28°C - 32°C = 60 mins     32°C - 35°C = 45 mins     Forms Free of Foreign Matter Prior to Pouring     Concrete Finished to Approved Tolerances  Audit Results and Comments	•	Actual Concrete Temperature				2.	3.
Amount of Admixture added     Amount of water added     Number of Cylinders Taken     Target Strength      Concrete Placement     Placement Method (Pump, Tremie, Chute, Other)      Sufficient Personnel for Finishing etc.     Approved Vibration Method     Back up Vibrators on Hand     Reinforcement Cover Maintained During Pour     Formwork Stable During Placing and Vibration     Concrete Placed and Compacted Within:     25°C - 28°C = 75mins     28°C - 32°C = 60 mins     32°C - 35°C = 45 mins     Provision for Closure of Access/Openings     Forms Free of Foreign Matter Prior to Pouring     Concrete Finished to Approved Tolerances  Audit Results and Comments	•	Target Slump 50 mm ± 10mm. Actual Slump					
Amount of Admixture added     Amount of water added     Number of Cylinders Taken     Target Strength      7. Concrete Placement     Placement Method (Pump, Tremie, Chute, Other)     Other)     Sufficient Personnel for Finishing etc.     Approved Vibration Method     Back up Vibrators on Hand     Reinforcement Cover Maintained During Pour     Formwork Stable During Placing and Vibration     Concrete Placed and Compacted Within:     25°C - 28°C = 75mins     28°C - 32°C = 60 mins     32°C - 35°C = 45 mins     Provision for Closure of Access/Openings     Forms Free of Foreign Matter Prior to Pouring     Concrete Finished to Approved Tolerances  Audit Results and Comments							
Amount of water added     Number of Cylinders Taken     Target Strength      7. Concrete Placement     Placement Method (Pump, Tremie, Chute, Other)     Sufficient Personnel for Finishing etc.     Approved Vibration Method     Back up Vibrators on Hand     Reinforcement Cover Maintained During Pour     Formwork Stable During Placing and Vibration     Concrete Placed and Compacted Within:     25°C - 28°C = 75mins     28°C - 32°C = 60 mins     32°C - 35°C = 45 mins     Provision for Closure of Access/Openings     Forms Free of Foreign Matter Prior to Pouring     Concrete Finished to Approved Tolerances  Audit Results and Comments							
Number of Cylinders Taken     Target Strength      7. Concrete Placement     Placement Method (Pump, Tremie, Chute, Other)      Sufficient Personnel for Finishing etc.     Approved Vibration Method     Back up Vibrators on Hand     Reinforcement Cover Maintained During Pour     Formwork Stable During Placing and Vibration     Concrete Placed and Compacted Within:     25°C - 28°C = 75mins     28°C - 35°C = 60 mins     32°C - 35°C = 45 mins     Provision for Closure of Access/Openings     Forms Free of Foreign Matter Prior to Pouring     Concrete Finished to Approved Tolerances  Audit Results and Comments	•						
Target Strength  7. Concrete Placement Placement Method (Pump, Tremie, Chute, Other)  Sufficient Personnel for Finishing etc. Approved Vibration Method Back up Vibrators on Hand Reinforcement Cover Maintained During Pour Formwork Stable During Placing and Vibration  Concrete Placed and Compacted Within:  25°C - 28°C = 75mins 28°C - 32°C = 60 mins 32°C - 35°C = 45 mins Provision for Closure of Access/Openings Forms Free of Foreign Matter Prior to Pouring Concrete Finished to Approved Tolerances  Audit Results and Comments	•				1.	2.	3.
7. Concrete Placement Placement Method (Pump, Tremie, Chute, Other) Sufficient Personnel for Finishing etc. Approved Vibration Method Back up Vibrators on Hand Reinforcement Cover Maintained During Pour Formwork Stable During Placing and Vibration Concrete Placed and Compacted Within: 25°C - 28°C = 75mins 28°C - 37°C = 60 mins 32°C - 35°C = 45 mins Provision for Closure of Access/Openings Forms Free of Foreign Matter Prior to Pouring Concrete Finished to Approved Tolerances Audit Results and Comments	•	Number of Cylinders Taken					
Placement Method (Pump, Tremie, Chute, Other)      Sufficient Personnel for Finishing etc.     Approved Vibration Method     Back up Vibrators on Hand     Reinforcement Cover Maintained During Pour     Formwork Stable During Placing and Vibration      Concrete Placed and Compacted Within:     25°C – 28°C = 75mins     28°C – 32°C = 60 mins     32°C – 35°C = 45 mins      Provision for Closure of Access/Openings     Forms Free of Foreign Matter Prior to Pouring     Concrete Finished to Approved Tolerances  Audit Results and Comments	•	Target Strength					
Placement Method (Pump, Tremie, Chute, Other)      Sufficient Personnel for Finishing etc.     Approved Vibration Method     Back up Vibrators on Hand     Reinforcement Cover Maintained During Pour     Formwork Stable During Placing and Vibration      Concrete Placed and Compacted Within:     25°C – 28°C = 75mins     28°C – 32°C = 60 mins     32°C – 35°C = 45 mins      Provision for Closure of Access/Openings     Forms Free of Foreign Matter Prior to Pouring     Concrete Finished to Approved Tolerances  Audit Results and Comments							
Other)  Sufficient Personnel for Finishing etc.  Approved Vibration Method  Back up Vibrators on Hand  Reinforcement Cover Maintained During Pour  Formwork Stable During Placing and Vibration  Concrete Placed and Compacted Within:  25°C - 28°C - 75mins 28°C - 32°C = 60 mins 32°C - 35°C = 45 mins  Provision for Closure of Access/Openings  Forms Free of Foreign Matter Prior to Pouring  Concrete Finished to Approved Tolerances  Audit Results and Comments							
<ul> <li>Approved Vibration Method</li> <li>Back up Vibrators on Hand</li> <li>Reinforcement Cover Maintained During Pour</li> <li>Formwork Stable During Placing and Vibration</li> <li>Concrete Placed and Compacted Within:  25°C - 28°C = 75mins  28°C - 32°C = 60 mins  32°C - 35°C = 45 mins</li> <li>Provision for Closure of Access/Openings</li> <li>Forms Free of Foreign Matter Prior to Pouring</li> <li>Concrete Finished to Approved Tolerances</li> <li>Audit Results and Comments</li> </ul>	•						
Back up Vibrators on Hand Reinforcement Cover Maintained During Pour Formwork Stable During Placing and Vibration  Concrete Placed and Compacted Within:  25°C - 28°C = 75mins 28°C - 32°C = 60 mins 32°C - 35°C = 45 mins  Provision for Closure of Access/Openings Forms Free of Foreign Matter Prior to Pouring Concrete Finished to Approved Tolerances  Audit Results and Comments	•	Sufficient Personnel for Finishing etc.					
Reinforcement Cover Maintained During Pour Formwork Stable During Placing and Vibration  Concrete Placed and Compacted Within:  25°C - 28°C = 75mins 28°C - 32°C = 60 mins 32°C - 35°C = 45 mins  Provision for Closure of Access/Openings Forms Free of Foreign Matter Prior to Pouring Concrete Finished to Approved Tolerances  Audit Results and Comments	•	Approved Vibration Method					
Formwork Stable During Placing and Vibration  Concrete Placed and Compacted Within:  25°C - 28°C = 75mins  28°C - 32°C = 60 mins  32°C - 35°C = 45 mins  Provision for Closure of Access/Openings  Forms Free of Foreign Matter Prior to Pouring  Concrete Finished to Approved Tolerances  Audit Results and Comments	•	Back up Vibrators on Hand					
Concrete Placed and Compacted Within:  25°C – 28°C = 75mins  28°C – 32°C = 60 mins  32°C – 35°C = 45 mins  Provision for Closure of Access/Openings  Forms Free of Foreign Matter Prior to Pouring  Concrete Finished to Approved Tolerances  Audit Results and Comments	•	Reinforcement Cover Maintained During Pour					
25°C – 28°C = 75mins 28°C – 32°C = 60 mins 32°C – 35°C = 45 mins  • Provision for Closure of Access/Openings • Forms Free of Foreign Matter Prior to Pouring • Concrete Finished to Approved Tolerances  Audit Results and Comments	•	Formwork Stable During Placing and Vibration					
28°C – 32°C = 60 mins 32°C – 35°C = 45 mins  • Provision for Closure of Access/Openings • Forms Free of Foreign Matter Prior to Pouring • Concrete Finished to Approved Tolerances  Audit Results and Comments	•	Concrete Placed and Compacted Within:					
32°C – 35°C = 45 mins     Provision for Closure of Access/Openings     Forms Free of Foreign Matter Prior to Pouring     Concrete Finished to Approved Tolerances  Audit Results and Comments							
Provision for Closure of Access/Openings     Forms Free of Foreign Matter Prior to Pouring     Concrete Finished to Approved Tolerances     Audit Results and Comments							
Forms Free of Foreign Matter Prior to Pouring     Concrete Finished to Approved Tolerances     Audit Results and Comments							
Concrete Finished to Approved Tolerances     Audit Results and Comments	•						
Audit Results and Comments	•						
	•			<u></u>			
Signature: Date		Audit Results	and	Com	ments		
Signature: Date							
	Sig	inature:		Date	,		

Doc ID	Version	Issued	Printed	Page
1.04–PCL Concrete Pour	2016.03	Sept 2016	19/09/2016	4 of 4