

# JOINT AIRDROP INSPECTION RECORD (PLATFORMS)

(See reverse for instructions)

1. UNIT BEING AIRDROPPED		2. AIRLIFT UNIT (*)		3. DEPARTURE AIRFIELD (ONLOAD)	
4. TYPE AIRCRAFT	5. AIRCRAFT SERIAL NO. (*)	6. ITEM DESCRIPTION		7. RIGGED IAW FM/TO NO	8. LOAD POSITION (*) OF
<b>LOAD DATA TAG INFORMATION</b>			9. WEIGHT	10. LENGTH	11. WIDTH
					12. HEIGHT

CHECK ONLY ITEMS APPLICABLE TO YOUR SPECIFIC LOAD	LOADING INSPECTION		CHECK ONLY ITEMS APPLICABLE TO YOUR SPECIFIC LOAD	LOADING INSPECTION	
	BEFORE	AFTER		BEFORE	AFTER
<b>13. EXTRACTION/DROGUE PARACHUTE AND RIGGING</b>			<b>19. CARGO PARACHUTE SYSTEM</b>		
A. CORRECT SIZE, BAG CLOSING TIES CORRECT			A. CORRECT NUMBER OF PARACHUTES (D-BAGS CLUSTERED)		
B. SAFETY LOOP/PENDULUM LINE ATTACHED			B. PARACHUTE SECURED TO LOAD, CONNECTED TO RELEASE WITH THREE-FOOT SLING (SINGLE PARACHUTE)		
C. SAFETY LOOP OVER BENT V-RING			C. RELEASE STRAPS ATTACHED TO CLEVIS AT PARACHUTE		
D. V-RINGS LOCKED IN PARACHUTE HOLDER			D. RESTRAINT STRAP PROPERLY SECURING PARACHUTE(S) AND ROUTED THROUGH RELEASE KNIFE(S)		
E. PENDULUM LINE PROPERLY SECURED (IAW -9 PROCEDURES)			E. RELEASE KNIFE SHARP, PROPERLY SAFETIED		
<b>14. EXTRACTION (ELB)/DROGUE LINE BAG (DLB)</b>			<b>20. M-1, M-2 OR M-3 PARACHUTE RELEASE ASSEMBLY</b>		
A. EXTRACTION/DROGUE LINE CORRECT LENGTH, LOOP, & TYPE			A. RELEASE POSITIONED CORRECTLY AND SECURED TO LOAD		
B. DROGUE/EXTRACTION LINE INSERTED INTO CLIPS AND/OR TIED TO PROPER RECESS			B. PARACHUTE CONNECTOR(S) SEATED IN RETAINER CLAMP		
C. ELB/DLB PROPERLY PACKED, BAG CLOSING TIES CORRECT			C. RELEASE TIMER KEYS EXTENDED, ARMING LANYARD WIRE SEATED, LANYARD SAFETIED AND SECURED TO PARACHUTE D-BAG HANDLE (TOGGLE LOCKSLIDE ALIGNED AND VISIBLE, M-3 ONLY)		
D. EXTRACTION/DROGUE LINE PROPERLY PLACED AND SECURED			<b>21. SUSPENSION SLINGS</b>		
E. DROGUE LINE CONNECTED TO TOWPLATE JETTISON LINK			A. ATTACHED TO COUPLER/CLEVIS/LINKS		
F. EXTRACTION LINE CONNECTED TO EXTRACTION SYSTEM			B. CORRECT LENGTH, LOOP, AND NUMBER		
<b>15. TOWPLATE EXTRACTION LINK</b>			C. ATTACHED TO LOAD OR PLATFORM		
A. DROGUE JETTISON LINK SAFETIED TO DROGUE EXTRACTION LINE			D. PROPERLY PADDED, ROUTED AND SECURED		
B. EXTRACTION LINK INSTALLED IN TOWPLATE			<b>22. GENERAL ITEMS</b>		
C. ENSURE LINK LATCH CAM FOLLOWERS LOCK OVER EXTRACTION LINK			A. LASHINGS UNIFORM TENSION AND BINDERS SAFETIED		
<b>16. DROGUE EXTRACTION SYSTEM</b>			B. ACCOMPANYING LOAD SECURED		
A. ELB BRIDLE ATTACHED TO EXTRACTION LINK			C. HONEYCOMB FLUSH AGAINST LOAD, GOOD CONDITION, PROPERLY ARRANGED		
B. CENTERLINE ATTACHED TO EXTRACTION LINK AND CONNECTOR LINK			D. PLATFORM NOT DAMAGED OR BOWED, BOTTOM CHECKED FOR CONDITION (CHECKED BEFORE OR DURING LOADING)		
C. ELB BRIDLE SECURELY ATTACHED TO ELB (6 PLACED) AND PARACHUTE DEPLOYMENT BAG BRIDLE(S)			E. HAZARDOUS MATERIAL CERTIFIED IAW TM 38-250/AFJMAN 24-204		
D. PARACHUTE(S) CLUSTERED AND TIED TO ELB			F. EMERGENCY RESTRAINT PROVISIONS ON THE PLATFORM/LOAD		
E. PARACHUTE(S) BAG CLOSING TIES AND MINIATURE KNIFE(S) INSTALLED AND SAFETIED			<b>23. OTHERS</b>		
F. KNIFE LANYARD(S) EQUAL EFFECTIVE LENGTH AND ATTACHED TO CONNECTOR LINK			(REF:		
G. PARACHUTE(S) ADAPTER WEB(S) ATTACHED TO CONNECTOR LINK			<b>24. ADS LOCKS</b>	A. NUMBER	B. SETTING
H. MAIN EXTRACTION LINE CONNECTED TO CONNECTOR LINK, CONNECTOR LINK SAFETIED TO PARACHUTE(S)			<b>25. BEFORE LOADING INSPECTION CERTIFICATION</b>	DATE/TIME COMPLETE /	
I. EXTRACTION LINE CORRECT LENGTH, LOOP, TYPE AND PROPERLY PACKED, BAG CLOSING TIES CORRECT			A. TRANSPORTED FORCE INSPECTOR		
J. PARACHUTE(S) AND ELB POSITIONED AND SECURED			UNIT (PRINT)	LAST NAME (PRINT)	INITIALS
K. CONNECTED TO EXTRACTION SYSTEM			SIGNATURE		
<b>17. SEQUENTIAL LOAD EXTRACTION PARACHUTE(S) AND ELB</b>			B. AIR FORCE INSPECTOR		
A. CORRECT SIZE, BAG CLOSING TIES CORRECT			UNIT (PRINT)	LAST NAME (PRINT)	INITIALS
B. PROPERLY PLACED, ATTACHED TO LOAD			SIGNATURE		
C. PENDULUM LINE/SAFETY LOOP PROPERLY ROUTED AND SECURED			<b>26. AFTER LOADING INSPECTION CERTIFICATION</b>	DATE/TIME COMPLETE /	
D. EXTRACTION LINE ATTACHED TO PARACHUTE, SAFETIED TO LOAD			A. TRANSPORTED FORCE INSPECTOR		
E. ELB PROPERLY PACKED, POSITIONED/SECURED, AND CONNECTED TO EXTRACTION SYSTEM			UNIT (PRINT)	LAST NAME (PRINT)	INITIALS
<b>18. EXTRACTION FORCE TRANSFER COUPLING (EFTC)</b>			SIGNATURE		
A. RELEASE CABLE ATTACHED TO ACTUATOR AND CABLE CLEVIS PIN INSTALLED			B. AIR FORCE INSPECTOR		
B. ACTUATOR MOUNTED, PINS INSTALLED AND SEATED			UNIT (PRINT)	LAST NAME (PRINT)	INITIALS
C. ACTUATOR ARM SAFETY PIN REMOVED AND STOWED			SIGNATURE		
D. LATCH AND ADAPTER SECURED TO THE LOAD, COUPLING LINK FULLY SEATED			<b>26. AFTER LOADING INSPECTION CERTIFICATION</b>	DATE/TIME COMPLETE /	
E. LATCH LOCKED, INDICATOR MARKS ALIGNED, RELEASE CABLE ATTACHED, CLEVIS PIN INSTALLED			A. TRANSPORTED FORCE INSPECTOR		
F. MARKED END OF SLOT IN LOCK LINK LINES UP WITH WHITE DIMPLE MARK ON LATCH BODY (60K)			UNIT (PRINT)	LAST NAME (PRINT)	INITIALS
G. PUSH DOWN ON LATCH PUSH ROD (NO RED VISIBLE ABOVE LATCH SIDE PLATE) (60K)			SIGNATURE		
H. CHECK ROLLER SHAFT DIMPLE CENTERED IN LATCH IN 1/4 INCH PEEPHOLE (60K)			B. AIR FORCE INSPECTOR		
I. CHECK LATCH LOCK FOR NO MOVEMENT BEYOND ALIGNMENT OF MARKED END OF SLOT WITH WHITE DIMPLE ON LATCH BODY (60K)			UNIT (PRINT)	LAST NAME (PRINT)	INITIALS
J. DEPLOYMENT LINE CORRECT LENGTH AND LOOP, ATTACHED TO COUPLING LINK AND PARACHUTE(S), PROPERLY ROUTED AND SAFETIED			SIGNATURE		
K. RELEASE CABLE CORRECT LENGTH, PROPERLY ROUTED AND SAFETIED			C. AIRCREW LOADMASTER		
L. ACTUATOR BRACKET PROPERLY MOUNTED			UNIT (PRINT)	LAST NAME (PRINT)	INITIALS
M. ACTUATOR COCKED AND ARM SAFETY PIN INSTALLED			SIGNATURE		
N. ACTUATOR REMOVED FROM MOUNTING BRACKET AND PLACED INBOARD FOR LOADING					

(\*) COMPLETE BLOCKS 2, 5 AND 8 DURING AFTER LOADING INSPECTION

### INSTRUCTIONS

Complete Joint Airdrop Inspection Record (*Platforms*) as required by AFJI 13-210/AF 59-4/OPNAVINST 4630-24b/MCO 13480.1A, and as detailed below:

Item 1. Enter the designation and geographic location of the military unit responsible for the equipment being tendered for airdrop.

\*Item 2. Enter the unit of aircraft commander (*complete during after-loading inspection*).

Item 3. Enter the designation of the locality from which the unit being airlifted is departing. (*Example: Bravo LZ, Eglin AFB FL.*)

Item 4. Enter the model and series of aircraft that will airlift the equipment to be airdropped. (*Example: C-130E.*)

\*Item 5. Enter the complete serial number (*tail number*) of the aircraft on which the equipment is loaded. (*Complete during after-loading inspections.*)

Item 6. Enter the nomenclature of the equipment tendered for airdrop. If additional space is required for mixed pieces of equipment, enter "see remarks" and describe the entire load in item 27. (*Example: HMMWV, ammunition, petroleum*)

Item 7. Enter the FM/TO number utilized in rigging the equipment tendered for airdrop.

\*Item 8. Enter the sequential position of each platform in the aircraft. For a three-platform load, the first platform loaded is Load #3. The last platform loaded is Load #1. (*Complete during after-loading inspection.*)

Item 9. Enter the total rigged weight of the platform, air items, and accompanying load as they appear on the load data tag.

Item 10. Enter the length of the platform or load, whichever is greater.

Item 11. Enter the width of the platform or load, whichever is greater.

Item 12. Enter the height of the platform and load from the bottom of the platform to the highest point on the load.

Item 13 through 22. Enter an X for each applicable item. Enter "NA" for non-applicable items. NOTE: If an entire major area is not applicable, it may be crossed out (X).

Item 23. Use the attachment in appropriate rigging manual and attach to inspection form.

Item 24. Inspect all locks affecting the platform for this pass and enter lock number(s) set into the platform and the setting on each lock.

Item 25. Enter local time and date of inspections. All entries, including signatures, must be complete and legible. Both the Transported Force and Air Force inspectors certify completion of the inspection. When the load is delivered to the aircraft, the aircrew loadmaster will ensure all items 1 through 12 are entered and correct, and ensure all checks in the before loading column (*items 13 through 22*) are entered. Ensure items 25A and B are completed.

Item 26. Enter local time and date of inspections. All entries including signatures, must be complete and legible. Both inspectors must certify completion. NOTE: After all inspections are completed, the aircrew loadmaster ensures that all applicable columns have been checked and affixes his signature certifying completion of all inspection requirements.

Item 27. Enter any comments pertaining to the load, loading difficulties encountered, or reason for rejection of the load. Also include any other pertinent facts concerning the load or delays. When inflight rigging is required, those items to be completed inflight will be annotated.

27. REMARKS