

SLING SAFETY INSPECTION RECORD

| | | | | | |
|---------------|--------|-------------|--------|-----------|-----------|
| Manufacturer: | Model: | Serial No.: | Reach: | Capacity: | Location: |
|---------------|--------|-------------|--------|-----------|-----------|

| COMPONENT UNIT OR PART | CODE | PROBLEM | S | A | R | CORRECTIVE ACTION NOTES |
|------------------------|------|---------|---|---|---|--|
| | | | A | D | E | - SAT = SATISFACTORY - ADJ = ADJUST - REP = REPAIR |
| | | | T | J | P | |

CHAIN SLINGS

CHAIN

| | | | | | | |
|-----------------------|---|--|--|--|--|--|
| Stretch or wear | D | | | | | |
| Grooving | D | | | | | |
| Twisted or bent links | D | | | | | |
| Cracks | D | | | | | |
| Gouges | D | | | | | |
| Corrosion | D | | | | | |
| Burns | D | | | | | |

MASTER LINKS

| | | | | | | |
|----------------------|-----|--|--|--|--|--|
| Stretch or wear | D | | | | | |
| Twisted or bent | D | | | | | |
| Cracks | D | | | | | |
| Gouges | D | | | | | |
| Corrosion | D | | | | | |
| Burns | D | | | | | |
| Hooks: | | | | | | |
| Defects or cracks | D/P | | | | | |
| Throat opening - 15% | D | | | | | |
| Twist - 10% | D | | | | | |

OTHER ITEMS

| | | | | | | |
|--------------------|--|--|--|--|--|--|
| Identification tag | | | | | | |
| Proper grade 8 | | | | | | |

WIRE ROPE SLINGS

| | | | | | | |
|--------------------------------|---|--|--|--|--|--|
| Wire rope: | | | | | | |
| Random broken wires/lay (10) | D | | | | | |
| Random broken wires/strand (5) | D | | | | | |
| Wear or scraping | D | | | | | |
| Kinking | D | | | | | |
| Crushing | D | | | | | |
| Bird caging | D | | | | | |
| Distortion of structure | D | | | | | |
| Heat damage | D | | | | | |
| Corrosion | D | | | | | |

END ATTACHMENTS

| | | | | | | |
|-----------------------|---|--|--|--|--|--|
| Proper wire rope cups | D | | | | | |
| Cracked | D | | | | | |
| Deformed | D | | | | | |
| Worn | D | | | | | |
| Corrosion | D | | | | | |

HOOKS

| | | | | | | |
|-------------------------|-----|--|--|--|--|--|
| Defects, cracks, twists | D/P | | | | | |
| Throat opening - 15% | D | | | | | |

| COMPONENT UNIT OR PART | CODE | PROBLEM | S A T | A D J | R E P | CORRECTIVE ACTION NOTES - SAT = SATISFACTORY - ADJ = ADJUST - REP = REPAIR |
|-------------------------------|------|--------------|--|-------------------------|-------------|---|
| SYNTHETIC WEB SLINGS | | | | | | |
| WEBBING | | | | | | |
| Acid or caustic burns | D | | | | | |
| Melting or charring | D | | | | | |
| Snags | D | | | | | |
| Punctures | D | | | | | |
| Tears | D | | | | | |
| Cuts | D | | | | | |
| Broken or worn stitches | D | | | | | |
| FITTINGS | | | | | | |
| Cracked | D | | | | | |
| Deformed | D | | | | | |
| Worn | D | | | | | |
| Corrosion | D | | | | | |
| HOOKS | | | | | | |
| Defects or cracks | D/P | | | | | |
| Throat openings - 15% | D | | | | | |
| Twist - 10% | D | | | | | |
| METAL, MESH SLINGS | | | | | | |
| MESH | | | | | | |
| Broken weld | D | | | | | |
| Broken brazed joint | D | | | | | |
| Reduction in diameter | D | | | | | |
| Lack of flexibility | D | | | | | |
| Handle: | | | | | | |
| Distortion of either handle | D | | | | | |
| Proper splices | D | | | | | |
| Abnormal wear | D | | | | | |
| Powdered fiber between strand | D | | | | | |
| Broken or cut fibers | D | | | | | |
| Variations in size | D | | | | | |
| Discoloration or rotting | D | | | | | |
| Distortion of hardware | D | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| REMARKS | | | | | | |
| 1. Inspection code intervals: | | | | | | |
| | D | daily | | | | |
| | M | monthly | | | | |
| | P | periodically | 1 to 12 month intervals, or as specifically recommended by the manufacturer. | | | |
| Date of Safety Inspection: | | | | Signature of Inspector: | | |